

1<sup>ST</sup> Floor, 91 Moreland Street, Footscray, VIC 3011  
P.O. Box 202, Yarraville VIC 3013  
Phone: (03) 9687 7655 Fax: (03) 9687 7680


**TEST REPORT FOR TECHNICAL SPECIFICATIONS**

**PRODUCT:** Belka Interior Wall Coating Material      **TEST NUMBER:** 8-655553-AN

<b>PACKAGING</b>	10 kilogram plastic bag
<b>DENSITY</b>	66kg per cubic meter
<b>SURFACE COVERAGE</b>	1 kilogram = 2/7 meters coverage
<b>THICKNESS OF COVERING</b>	0.5mm to 2mm per square meter
<b>DRYING TIME</b>	12 to 48 hours (depending on ventilation, temperature & humidity)
<b>SHRINKAGE</b>	0% on testing
<b>ELASTICITY</b>	3-4.5mm per square meter
<b>INSULATION - THERMAL</b>	Coefficient of thermal conductivity 0.062kcal/mhc
<b>INSULATION - ACOUSTIC</b>	An average 17 to 5000 Hz at 24 db
<b>FIRE RESISTANCE</b>	Inflammable – Heat release rate of less than 50W/m2
<b>ANTI STATIC PROPERTIES</b>	Dust absorption/attraction reduced up to 99%
<b>APPLICATION</b>	One coat with a trowel
<b>COMPOSITION</b>	Natural Fibers, mineral flakes and natural adhesive



DR GRAEME BECK  
TECHNICAL SERVICES MANAGER



RUDI SENDELBECK  
DIRECTOR